

200 SERIES ADDRESSABLE FIRE ALARM SYSTEM



Intelligent Addressable Optical Smoke Detector FF O200

- ▶ Stable operation with advanced digital signal processing
- ▶ Automatic compensation
- ▶ Short circuit isolator
- ▶ Double dust trap
- ▶ 360° view
- ▶ Made in Italy
- ▶ EN54-7 and EN54-17 Standard
- ▶ LPCB Approved



Intelligent Addressable Heat Detector FF T200

- ▶ Stable operation with advanced digital signal processing
- ▶ Automatic compensation
- ▶ Short circuit isolator
- ▶ Double dust trap
- ▶ 360° view
- ▶ Extended temperature range
- ▶ Made in Italy
- ▶ EN54-5 and EN54-17 Standard
- ▶ LPCB Approved



Intelligent Addressable Optical and Heat Detector FF OT200

- ▶ Stable operation with advanced digital signal processing
- ▶ Automatic compensation
- ▶ Short circuit isolator
- ▶ Double dust trap.
- ▶ 360° view
- ▶ Extended temperature range
- ▶ Made in Italy
- ▶ EN54-5, EN54-7 and EN54-17 Standard
- ▶ LPCB Approved



Intelligent Addressable Electronic Sounder and Beacon FF ESF100 + FF LX200

- ▶ Maximum performance with high-power LED
- ▶ Red and white LED option
- ▶ Shallow base IP43
- ▶ Deep base IP65 versiyon
- ▶ Base locking system
- ▶ EN54-3 and EN54-23 Standard
- ▶ LPCB Approved



Addressable Call Point FF-VB200

- ▶ Surface mounted and flush mounted
- ▶ Resettable
- ▶ Short circuit isolator
- ▶ Made in Italy
- ▶ EN54-11 and EN54-17 Standard
- ▶ LPCB Approved



Intelligent Addressable Relay Output Module FF MC220

- ▶ 1 output relay
- ▶ Short circuit isolator
- ▶ Made in Italy
- ▶ EN54-18 and EN54-17 Standard
- ▶ VDS Approved



Intelligent Addressable Input / Output Module FF MIC200

- ▶ 1 output / 1 input
- ▶ Short circuit isolator
- ▶ 24V Powered
- ▶ Made in Italy
- ▶ EN54-18 and EN54-17 Standard
- ▶ VDS Approved



Intelligent Addressable Output Module FF MC200

- ▶ 1 output
- ▶ Short circuit isolator
- ▶ 24V Powered
- ▶ Made in Italy
- ▶ EN54-18 and EN54-17 Standard
- ▶ VDS Approved



Intelligent Addressable Input Module FF MI200

- ▶ 1 input contact
- ▶ Short circuit isolator
- ▶ Made in Italy
- ▶ EN54-18 and EN54-17 Standard
- ▶ VDS Approved



Detector Buzzer Socket FF BS200BB

- ▶ 75dB / 3m sound level
- ▶ 5mA alarm